

# EXPLORER™ 700

## Technical Specifications

**Meets or exceeds Inmarsat specifications for operation on the Inmarsat Broadband Global Area Network (BGAN).**

### General

Type:	EXPLORER™ 700
Max. IP data rate, Rx/Tx:*	492kbps/492kbps (simultaneously)
Streaming IP:	32, 64, 128, 256kbps
Weight:	
Total (incl. battery):	3.2kg/7.0lbs
Antenna:	1.7kg/3.7lbs
Transceiver (incl. battery):	1.5kg/3.3lbs
Size:	
Total:	H: 29.0cm/W: 39.9cm/D: 5.1cm H: 11.3inches/W: 15.6inches/D: 2.0inches
Antenna:	H: 29.0cm/W: 39.9cm/ D: 5.1cm H: 11.3inches/W: 15.6inches/D: 2.0inches
Transceiver:	H: 28.0cm/W: 22.8cm/D: 4.0cm H: 10.9inches/W: 8.9inches/ D: 1.6inches
LCD display:	Graphical high resolution Back lit 2 x 16 characters in text mode
MMI:	Four navigation keys and power button Audio and LCD pointing aids LED indicators Launch pad and web configuration
Battery:	Lithium ion, rechargeable
Stand-by time:	36h, 25°C/77°F
Tx time, max.:	2h30m @ 144kbps (158MB), 25°C/77°F 1h30m @ 492kbps (324MB), 25°C/77°F
Rx time, max.:	3h30m @ 492kbps (756MB), 25°C/77°F
Min. charge cycles:	300
Recharge time:	2h30m
Charge temperature:	0°C to +45°C/32°F to +113°F
Frequencies:	
Inmarsat:	
Rx:	1525.0 – 1559.0MHz
Tx:	1626.5 – 1660.5MHz
GPS:	1575.42MHz
EIRP:	20dBW ±1dB

### Environmental Conditions

Operating temperature:	-25°C to +55°C -13°F to +131°F
Storage temperature:	-40°C to +80°C (excl. battery) -40°F to +176°F (excl. battery)
Battery storage temperature:	
1 month:	-20°C to +60°C/-4°F to +140°F
3 months:	-20°C to +45°C/-4°F to +113°F
1 year:	-20°C to +20°C/-4°F to +68°F
Relative humidity:	95% non-condensing at +40°C/+104°F
Robustness:	0.5 m/1.64 ft drop on concrete (operational, 95% survival)
Water & dust:	
Transceiver:	IP-52
Antenna:	IP-66

### Power

DC input range:	10-32VDC
Power consumption*:	
Standby mode:	1.2W (typical)
Transmit mode:	18W (typical)
During charging:	60W (max.)
Connector type:	2.5/5.5mm switch craft RAPC 712
AC/DC Adapter:	
Input:	100-240VAC, 47-63Hz, 60W
Output:	19VDC
Built-in Bluetooth handset charger:	6.2V, 350mA

### Solar Panel

Type:	12V unregulated solar panels, built-in PPT for solar panel regulation
Max. open circuit voltage:	32V
Max. PP:	28V

### Transceiver/Antenna Interface

Max. cable length:	70m/229ft, single cable
Connector type:	TNC-QN
Max. cable loss:	1.4Ω/20dB

\* Performance depends on a wide range of factors and actual usage.

# Thrane & Thrane

## WLAN Access Point

Standard:	IEEE 802.11 a/b/g
Antenna:	Dual space diversity antennas integrated in transceiver unit
Max. coverage outdoor:*	100m/328ft
Max. datarate:*	54Mbps

## LAN Interface, 2-port

Connector type:	RJ-45, auto cross over MDI/MDI-X
Standard:	ISO/IEC 8877:1992. and IEEE 802.3 1998 edition
Max. cable length:	100m/328ft (Cat5 UTP)
Data rate:	10/100Mbps

## Bluetooth Interface

Version:	1.2
Standard:	Power Class 1
Antenna:	Integrated in transceiver unit
Max. coverage:*	
Outdoor:	100m/328ft
Max. devices connected:	7 handsets, 1 PC, etc.
Profiles supported:	Cordless handset, serial port, dial-up networking
Frequencies:	2400.0 – 2483.5MHz

## ISDN Interface, 2-port

Connector type:	RJ-45
Max. units pr. I/F:	8, max. total power supplied 1W
Datarate:	
Voice:	4kbps
Data:	64kbps
Audio:	3.1kHz

## Analogue Phone/Fax Interface, 2-port

Connector type:	RJ-11
Impedance:	600Ω

## USB Interface

Version:	1.1, slave
Connector type:	B plug
Max. data rate:	12Mbps
Max. cable length:	5m/16.4ft

## I/O Interface

Connector type:	Screw terminal plug
Function:	2 input/output
Input:	TTL-level, voltage 0-32V
Output:	Sinking current max. 50mA, voltage 0-32V

## Certifications

CE
FCC
GMPCS

## Package

EXPLORER™ 700 transceiver unit incl. lithium ion battery
EXPLORER™ 700 antenna
Antenna cable
ISDN/LAN cable
USB cable
115/230VAC power adapter
Getting started kit

## Accessories

Bluetooth handset and charger	
Antenna mounting kit	
Antenna cables:	<5m, 3mm coax cable
	<30m, 5mm coax cable,
	<70m, 10mm coax cable
Car charger cable	
Softbag	
Spare lithium ion battery	

\* Performance depends on a wide range of factors and actual usage.

